Module Introduction

51.2V200AH 10240WH



- *All-time monitor*
- *Safety for home*
- *Long Lifespan*
- *Flexible capacity*
- *Easy Installation*

Normal	
Model	OTW48200
Battery Type	LifePO4(LFP)
Nominal Voltage(V)	51.2V
Nominal Capacity(WH)	10240WH
Usable Capacity(WH)	9216WH
Design Life	10+ Years (25℃/77F)
Physical	
Dimension(mm)	577*237*985
Weight(kg)	112.4
Electrical	
Cycle Life	>6000 cycles @25℃±2℃, 80%DOD
Discharge Voltage(V)	44.8
Charge Voltage(V)	56.8
Charge/Discharge Current(A)	80A(Recommended)
	100A(Max)
Internal Resistance	≤30mΩ
BMS	
Power Consumption	<2W (Work) <100mW(Sleep)
Monitoring Parameters	System voltage, Current, cell voltage, cell temperature, module temperature
SOC	Intelligent algorithm
Communication	CAN/RS-485
Operation	
Operating Temperature Range	Charge Temperature 0℃~60℃; Discharge Temperature -20℃~60℃;
Transport or Storage Temperature Range	-20℃~45℃
Humidity	15%~85% (No Condensing)
Warranty	
Product Warranty	5 Years
Performance Warranty	10 Years

Work With

SMA

Deye 德業®

solis

victron energy

Growatt

固德威 GOODWE

Voltronic Power

SOFAR SOLAR